



RLA Carpet Seam Adhesive

PRODUCT DESCRIPTION:

RLA Carpet Seam Adhesive is an extrudable solvent based neoprene contact type adhesive. This adhesive is designed to bond carpet seams together, once cured displays good water and heat resistance.

FOR BONDING:

Carpet seam edges together where carpet is either directly bonded to the floor or double bonded over underlay..

APPLICATION:

Seams must be clean, dry and free from adhesive. Starting at one end of the seam, apply a 3.0mm bead along the length of the seam using a Seam Adhesive Applicator.

CLEAN UP:

To clean up equipment and adhesive spills, use a suitable cleaning solvent.

COVERAGE:

Approximately 40- 50 LM per 1 litre depending on applicator and site conditions.

CONTAINER SIZES

1 litre plastic bottle

SHELF LIFE / STORAGE:

6 months when stored in original unopened packaging
To be stored in a dry area off the ground.

SAFETY & HANDLING

A Safety Data Sheet is available on request.
Product is classified as HAZARDOUS GOODS. According to the WHS Regulations and the ADG Code.
This product is classified UN 1133, D.G. Class 3, Hazchem 3 YE Packaging Group II
This product is FLAMMABLE should be stored accordingly and in line with correct regulations.
Shelf life is one year from date of manufacture if unopened. Keep container tightly closed. Store Locked up. Keep container in a cool well ventilated place away from sources of heat.

RISK

Causes skin irritation, Causes serious eye irritation May cause damage to organs through prolonged or repeated exposure.
Suspected of damaging fertility or the unborn child
Safety Data Sheet Available on request

TYPICAL PROPERTIES

Appearance: Honey like
Base: Neoprene Rubber
Solids: Approx. 22%
Viscosity: 1,800 Cps (Approx)
Flammable: Flammable
Toxic: Toxic

SAFETY DIRECTIONS

KEEP away from HEAT/SPARKS/OPEN FALMES/HOT SURAFGES – NO SMOKING

Keep container tightly closed . Keep container in a cool well ventilated place.

Use only non-sparking tools

During the installation process , adequate ventilation of the work area should be maintained without causing the entry of contaminants to other parts of the building.

In case if insufficient ventilation wear suitable respiratory equipment. Wear protective gloves, eye and face protection.

Use Personal Protective Equipment as required. Take precautionary measures against static discharges. Wash thoroughly after handling. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid Eyes and Skin contact .IF ON SKIN Remove immediately all contaminated clothing and rinse skin with water. IF ON SKIN wash with plenty of soap and water .If skin irritation occurs get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF IN EYES Rinse carefully with water for several minutes. If eye irritation persists get medical advice/attention. If exposed or concerned get medical advice/attention

Person who are sensitive to odours and or chemicals should avoid the work area.

IN case of FIRE use foam to extinguish.

Safety Data Sheet Available on request

Warranty Statement:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attention Customer Service)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: January 2021