



Waterproofer

Economical water resisting admixture for concrete and masonry.

Integral water resisting admixture for concrete and masonry, above or below ground. Recommended for use where coloured mortar or integral floor colours are used

FEATURES & BENEFITS:

- · Water Based formula safe to use.
- Economical solution.
- Improved mix workability.
- Improves water resistance.
- Reduce porosity of mortar mix.
- Improved durability.
- Suitable for after trades

APPLICATION INSTRUCTIONS:

Preparation

All surfaces to be treated must be free of oil, grease or other contamination which may inhibit the bond of the render. Any looks concrete should be removed prior to the application of any mortar or render containing Waterproofer.

Mixing

Waterproofer is suitable for application straight out of the container without prior mixing.

Application

Add the Waterproofer to the mix at the rate of one to four litres per 40kg of Portland cement. Add the Waterproofer to the gauge water rather than directly to the mix wherever possible. Do not premix with any admixture, always add any other admixtures separately to the mix.

Curing

Mortars and renders modified with Waterproofer should be cured with either Curecon W or Curecon PW.

CLEAN UP:

Clean all equipment with water immediately after use.

ESTIMATING:

Approximate Material Usage

One to two litres per 40KG of Portland cement.

PACKAGING:

Waterproofer is supplied in 20 Litre and 200 Litre sizes.

STORAGE:

Waterproofer is a water based product which must be stored in the original unopened containers.

PRECAUTIONS:

Where temperatures are less than 5° C or greater than 35° C are encountered, contact our technical staff for specific advice.

Any contact with eyes or skin should be washed off with soap and clean water. Do NOT use solvent. If swallowed seek immediate medical treatment. Protective gloves, goggles and clothing should be worn.

Do not use lime in water resistant mixes containing Waterproofer. Avoid excessive use of Waterproofer in doses greater than those recommended.

AVAILABILITY:

Waterproofer is available Australia wide through the RLA Polymers distributor network. Please contact our head office on 1800 242 931 to find out where your nearest stockist will be.

TECHNICAL SUPPORT:

RLA Polymers manufactures a comprehensive range of high quality, high performance construction products. In addition, RLA Polymers offers technical support and on-site advice to specifiers, end users and contractors. Please contact your RLA Polymers sales representative or RLA Head Office for this service.

PRODUCT DATA	
Specific Gravity @ 25°C	0.98 gm/ml
Ph	9.5-10.5

Issue Date: 09/6/2020 Version: 1



RLA Polymers Pty Ltd ACN 004 709 915

Head Office 215 Colchester Road Kilsyth, Victoria, 3137 Tel: 1800 242 931

New South Wales 363 Wentworth Ave Pendle Hill, N.S.W, 2145 Queensland 57 Fulcrum Street Richlands, QLD, 4077 Western Australia 24 Hanwell Way Bassendean, W.A, 6054 Tel: 08 9279 8911



For the latest TDS information please visit rlapolymers.com.au