



CURECON AA

WATER BASED, ALIPHATIC ALCOHOL FINISHING COMPOUND



DESCRIPTION

CURECON DOUBLE A is a water based, aliphatic alcohol finishing compound designed for use on plastic (freshly poured and screeded) concrete, to reduce the rapid evaporation of water during finishing operations. CURECON AA will not normally interfere with subsequent toppings and common finishes including tiling, render and surface coatings

FEATURES & BENEFITS

- Water based
- Reduces evaporation of water from the concrete surface
- Improves finishing properties in adverse weather conditions
- · Reduces shrinkage cracking through premature drying
- Does not interfere with following trades and finishes

USES

To reduce rapid evaporation of water from freshly poured concrete

APPLICATION

Mixing:

- Stir contents thoroughly before use
- Pre-dilute CURECON AA with clean water in a clean mixing pail or vessel at the following ratio:

1 part CURECON DOUBLE A 9 parts water (by volume)

• Mix thoroughly to combine prior to application.

Application

- · Application is by low pressure backpack type spray
- Decant mixed solution into sprayer and apply evenly over the concrete surface immediately after screeding ensuring full coverage
- CURECON AA should be re-applied each time the surface is broken (I.e. screed, bull float, troweling).

COVERAGE

Approximately 1litre per 5-7m²

CLEAN UP

- · Clean all equipment with water while wet
- Once dry, use a 1:1 solution of methylated spirits and mineral turpentine to remove

SHELF LIFE / STORAGE

- 12 months when stored in original unopened packaging
- Best stored in a dry area at room temperature
- · Keep off cold floors and out of direct sunlight
- Curecon AA may "layer" when stored for extended periods of time. Stir thoroughly before use

CONTAINER SIZES

· 20litre containers and 200Litre drums

PRECAUTIONS

- Do not apply CURECON AA to surfaces with excessive bleed
- Mix only the amount of product likely to be needed for each application. Mixed CURECON AA is not recommended to be stored.

| PRODUCT INFORMATION: | |
|----------------------|------------------------------|
| Appearance | Thin liquid |
| Colour | Wet: Pale Blue Dry: Clear |
| Specific Gravity | 1.0/cm3 |

HEALTH & SAFETY

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.







WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturer's instructions, and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: 1800 242 931

EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsyth Victoria 3137

(Attention Customer Service)

WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Version: 01 Issue date: 13/11/2023

RLA Polymers Pty Ltd ACN 004 709 915

Head Office 215 Colchester Road Kilsyth, Victoria, 3137 Tel: 1800 242 931 New South Wales 5A 246 Miller Road Villawood, NSW, 2163 Queensland 57 Fulcrum Street Richlands, QLD, 4077 South Australia Unit 2/7 Berger Road Wingfield ,SA, 5013 Western Australia 24 Hanwell Way Bassendean, W.A, 6054 Tel: 08 9279 8911